



CVT FLUID

APPLICATION GUIDE

Supporting Data Available To Demonstrate Acceptable Performance For The Following Applications

APPLICATION:

SUITABLE FOR USE

Audi Multitronic	Yes
BMW Mini Cooper EZL 799A/ 83 22 0 136 376/ 83 22 0 429 154	Yes
Chery CVT	Yes
Chery WCF-1/Shell SL 2100.	Yes
Citroen PSA Standard 9735EF	Yes
Daihatsu AMMIX CVTF DFE	Yes
Daihatsu AMMIX CVT Fluid DC	Yes
Daihatsu AMMIX CVT Fluid DFC	Yes
Daihatsu Fluid TC.	Yes
Dodge/Jeep/Chrysler NS-2	Yes
Dodge/Chrysler/Jeep/Mopar CVT+4.	Yes
Fiat Tutela Car CVT N.G	Yes
Ford WSD-M2C-199A	Yes
Fujijyuuko i-CVTF FG	Yes
GM/Saturn DEX-CVT, GM 1940713 and 1940714.	Yes
GM/Saturn CVTF I-Green2	Yes
GM VT40 /GM HP CVT	Yes
Honda HMMF Ultra (for CVT without a starting clutch)	Yes
Honda HCF2	Yes
Honda Z-1 (CVT without starting clutch).	Yes
Honda CVT (not recommended for any Honda with starting clutch).	Yes
Honda Ultra HEVF-Type 1	Yes
Hyundai/Kia CVT-1, SP CVT-1 and CVT-J1	Yes
Hyundai/Kia SP III (CVT model).	Yes
Idemitsu CVTF-EX1	Yes
Lexus Fluid TC, Fluid FE.	Yes

Not to be used for DCT applications.

For best results, perform CVT exchange regularly according to vehicle manufacturer recommended normal/severe service intervals.



We're the Manufacturer!



Toll Free 877-290-3950



www.SolidStart.com



CVT FLUID

APPLICATION GUIDE

Supporting Data Available To Demonstrate Acceptable Performance For The Following Applications

APPLICATION:

SUITABLE FOR USE

Mazda JWS 3320	Yes
MG Rover EM-CVT	Yes
Mini Cooper EZL 799/EZL 799A/ZF CVT V1	Yes
Mitsubishi CVT Fluid-MA1	Yes
Mitsubishi CVTF-J1 (MMC Diaqueen CVT Fluid J1)	Yes
Mitsubishi CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid J4 and J4+)	Yes
Mitsubishi CVTF ECO J4	Yes
Mitsubishi (Diaqueen) SP-III (CVT model only)	Yes
Nissan NS-1	Yes
Nissan NS-2	Yes
Nissan NS-2V	Yes
Nissan NS-3	Yes
Nissan N-CVT	Yes
Opel/Vauxhall 7-speed CVT, 95529854	Yes
Perodua D-CVT	Yes
Peugeot PSA Standard 9735EF	Yes
Punch CVTF-EX1 for Punch VT2/VT3 Transmissions	Yes
Renault Elf Matic CVT	Yes
Renault CVT CK/SK/FK	Yes
Shell Green 1V	Yes
Subaru iCVT	Yes
Subaru iCVT FG	Yes
Subaru ECVT	Yes
Subaru Lineartronic chain CVT and CVT II Fluid, K0425Y0710 & K0425Y0711	Yes
Subaru Lineartronic chain CVT 3 Fluid	Yes
Subaru Lineartronic High Torque (HT) CVT Fluid, CV-30, K0421Y0700	Yes

Not to be used for DCT applications.

For best results, perform CVT exchange regularly according to vehicle manufacturer recommended normal/severe service intervals.



We're the Manufacturer!



Toll Free 877-290-3950



www.SolidStart.com



CVT FLUID

APPLICATION GUIDE

Supporting Data Available To Demonstrate Acceptable Performance For The Following Applications

APPLICATION:

SUITABLE FOR USE

Subaru High Torque CVTF-LV	Yes
Suzuki CVTF TC	Yes
Suzuki CVTF 3320	Yes
Suzuki CVTF 4401	Yes
Suzuki NS-2	Yes
Suzuki CVT Green 1 & 2	Yes
Suzuki CVT Green 1V	Yes
Toyota CVTF TC	Yes
Toyota CVTF FE	Yes
Volvo CVT 4959	Yes
VW/Audi TL 521 16 (G 052 516)	Yes
VW/Audi TL 521 80 (G 052 180)	Yes
Zotye CVTs	Yes

eMobility Claims/Applications

Ford Escape Hybrid with eCVT	Yes
Honda e:HEV	Yes
Honda iMMD	Yes
Jatco JR712E	Yes
Jatco CVT 8 Hybrid	Yes
Mazda SKYACTIVE-HYBRID	Yes
Nissan e Power	Yes
Nissan Altima Hybrid	Yes
Toyota THSII/Toyota Prius	Yes
Toyota THS 5th Gen. / Toyota Noah, Voxy etc.	Yes

Not to be used for DCT applications.

For best results, perform CVT exchange regularly according to vehicle manufacturer recommended normal/severe service intervals.



We're the Manufacturer!



Toll Free 877-290-3950



www.SolidStart.com